



€ 31.782 VAT excluded

L 35 ADAPTOR		L35 F	L 35 H
Wheelbase	F	2760	3360
Overall length	OAL	5295	6015
Body lenght min. ⁽¹⁾	W	3545	4265
Body lenght Max. ⁽¹⁾	W	3915	4530
Rear overhang	ROH	1435	1555
Chassis height	EH		715
Overall height	OH	2150	2160
Rear axle width	BW		1860
Cab width ⁽²⁾	OW		1815
Body width ⁽³⁾	6,1		2120
Front axle to back of cab	D min		650
Front overhang	FOH		1100
Frame internal size	LaC		700
Front track	AW		1400
Rear track	CW		1425
Minimum Road Clearance	HH		180
Turning diameter (m) ⁽⁴⁾	Dia	10,0	11,9
WEIGHT (kg)			
Unladen weight ⁽⁵⁾		2200	2250
Unladen weight front axle		1530/670	1550/700
Minimum weight vehicle equipped			2585
Gross Vehicle Weight (GVW)			3500
Front/rear total weight			2100 / 2435
Max trailer weight braked/Max trailer weight unbraked			3500 / 750

1. The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
2. Excluding turn signal and side mirrors
3. Possible widths with optional mirror brackets 1860/1945 – 1945/2120 – 2120/2275
4. Curb to curb turning diameter
5. The Unladen weight include spare wheel, full fuel tank and driver, optional excluded. NEES II + 35 kg.

PROVISIONAL VERSION: All data must be confirmed by the type approval certificate.

L 35 ADAPTOR - Wheelbase (mm) F 2760 - H 3360

MAY 2021

€ 31.782 (**)

Equipment	NEES 2 (only Wheelbase H)	€ 1290 (**)
(**)VAT excluded		
Standard features		
<ul style="list-style-type: none"> • EGR - DPD - SCR • MID display • Engine exhaust brake • Suspended seat • Immobilizer 	<ul style="list-style-type: none"> • Central locking with remote control • Power operated windows • Day-time running lights • Seat belt buzzer 	<ul style="list-style-type: none"> • Radio DAB+ with USB • Fog lamps Fr and Rr • Head lamps control levelling • Steering adjustable (tilting and height) • Reverse warning buzzer
Optional	. Air conditioning	€ 1089 (**)
Engine	ISUZU 4JJ1E6N 4 cylinders. Intercooler, common-rail with direct injection Variable-geometry turbocharger DISPLACEMENT 2999 cm ³ POWER 110kW (150 hp) 2800 rpm. TORQUE. 375 Nm 1600 – 2800 rpm EMISSIONS REGULATIONS EURO VI OBD-D + Safety Pack.	
Safety systems	ABS with BAS (Brake Assist System) ESC (Electronic Stability Control) with ASR SRS Driver Airbag	
Tank	68 L Wheelbase F – 93 L Wheelbase H	16 L Ad-Blue®
Gearbox and Final drive ratio	5 gear MYY5A – 5.315 - 2.908 - 1.558 - 1.000 - 0.721; Reverse 5.068; Final gear ratio 3.909 (43/11)	
Transmission control	Manual	NEES 2
Dimensions of the chassis	Width 50 mm, Height 180 mm, Thickness 4 mm	
Number of seats	3	
Axle	2 the rear one with twin wheels.	
Tires	Front 205/75 R16C simple. Rear 205/75 R16C dual.	
Brakes	Front and rear: ventilated discs with asbestos-free linings. Hydraulic system, with vacuum brake booster EEC standards with ABS, independent circuits on both axles. Drum parking brake on the transmission shaft.	
Suspensions	Front: Independent suspension with coil spring and double wishbone. Rear: Multi semi elliptical alloy steel leaf spring. Hydraulic double acting shock absorbers.	
Electric system	Nominal voltage 24V - Generator 90A - 2 x Battery 70Ah	

PROVISIONAL VERSION: All data must be confirmed by the type approval certificate.