



€ 41.280 VAT excluded

P 65		P65 H	P 65 K
Wheelbase	X	3395	3845
Overall length	K	6090	6735
Body length min. ⁽¹⁾	W	4270	4915
Body length Max. ⁽¹⁾	W	4555	5205
Rear overhang	Y	1585	1780
Chassis height	T		800
Overall height	H		2250
Rear axle width	L		1990
Cab width ⁽²⁾	L1		2040
Body width ⁽³⁾	C		2345
Front axle to back of cab	D min		710 ⁽⁶⁾
Front overhang	A		1110
Frame internal size	I		750
Front track	C1		1680
Rear track	C2		1525
Minimum Road Clearance	-		210
Turning diameter (m) ⁽⁴⁾	-	12,7	14,2
WEIGHT (kg)			
Unladen weight ⁽⁵⁾		2600	2640
Unladen weight front axle		1730/870	1750/890
Gross Vehicle Weight (GVW)		6500	
Front/rear total weight		3100 / 4600	
Max trailer weight unbraked/Max trailer weight braked		750 / 3500	

1. The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
2. Excluding turn signal and side mirrors
3. Possible widths with optional mirror brackets 2040/2170 – 2170/2345 – 2345/2500
4. Curb to curb turning diameter
5. The Unladen weight include spare wheel, full fuel tank and driver, optional excluded. NEES +35 Kg (25/10)
6. NEES II 650.

P 65 - Wheelbase (mm) H 3395 - K 3845

FEBRUARY 2021

€ 41.280(**)

Equipment	NEES 2	€ 1290 (**)
-----------	--------	-------------

(**)/VAT excluded

Standard features

- EGR - DPD - SCR
- MID display
- Engine exhaust brake
- Reverse warning buzzer
- Immobilizer
- Central locking with remote control
- Power operated windows
- Suspended seat
- Side mirrors heated and electric
- Radio DAB+ with USB
- Head lamps control levelling
- Day-time running lights
- Steering adjustable (tilting and height)
- Speed limiter (90km/h)

Optional

- Air conditioning € 1089 (**)
- Wheelbase modified Ask to your dealer
- Body builder Controller € 354 (**)

Engine

ISUZU 4JJ1E6N Diesel Engine 4 cylinders.

Intercooler, common-rail with direct injection
Variable-geometry turbocharger
DISPLACEMENT 2999 cm³
POWER 110kW (150 hp) 2800 rpm
TORQUE 375 Nm 1600 – 2800 rpm
EMISSIONS REGULATIONS EURO VI OBD-D.

Safety systems

ABS
ESC (Electronic Stability Control) with ASR
LDWS
AEBS
SRS 2 Airbag (Driver/Pass.)

Tank

90 L 16 L Ad-Blue®

Gearbox and Final drive ratio

6 gear MYY6S – 5.979 - 3.434 - 1.832 - 1.297 - 1.000 - 0.759;
Reverse 5.068;
Final gear ratio 4.556 (41/9)

Transmission control

Manual NEES 2

Dimensions of the chassis

Width 70 mm, Height 214 mm, Thickness 5 mm

Number of seats

3

Axle

2
the rear one with twin wheels.

Tires

Front 215/75 R17,5C simple.
Rear 215/75 R17,5C dual.

Brakes

Front and rear: ventilated discs with asbestos-free linings. Hydraulic system, with vacuum brake booster EEC standards with ABS, independent circuits on both axles. Drum parking brake on the transmission shaft.

Suspensions

Front and rear: Multi semi elliptical alloy steel leaf spring. Hydraulic double acting shock absorbers.

Electric system

Nominal voltage 24V - Generator 90A - 2 x Battery 70Ah