


Suspensions air Série Bleu OBD-E (14 ton)

OBD-E



€ 67.913 VAT excluded

	F 14	F 14 J	F 14 L	F 14 N	F 14 Q
Wheelbase	F	3790	4360	4990	5320
Overall length	OAL	6610	7480	8380	8680
Body lenght min. ⁽¹⁾	W	4725	5595	6495	6795
Body lenght Max. ⁽¹⁾	W	5025	5895	6795	7095
Rear overhang	ROH	1645	1945	2215	2185
Chassis height	EH		785		
Overall height	OH	2600	2595	2595	2595
Rear axle width	BW		2225		
Cab width ⁽²⁾	OW		2195		
Body width ⁽³⁾	6,1		2535		
Front axle to back of cab	D min		710		
Front overhang	FOH		1175		
Frame internal size	LaC		840		
Front track	AW		1800		
Rear track	CW		1670		
Turning diameter (m) ⁽⁴⁾	Dia	13,7	15,5	17,5	18,6
WEIGHT (kg)					
Unladen weight ⁽⁵⁾		4270	4330	4400	4410
Unladen weight front axle		2685/1585	2735/1595	2775/1625	2790/1990
Gross Vehicle Weight (GVW)		14000			
Front/rear total weight		5000 / 9000			
Max trailer weight braked / Max trailer weight unbraked		3500 / 750			

1. The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
2. Excluding turn signal and side mirrors
3. Possible widths with optional mirror brackets 2220/2286 – 2286/2406 – 2406/2500 – 2500/2535
4. Curb to curb turning diameter
5. The Unladen weight include spare wheel, full fuel tank and driver, optional excluded. NEES II + 25 kg.

PROVISIONAL VERSION: All data must be confirmed by the type approval certificate.

F 14 - Wheelbase (mm) J 3790 - L 4360 - N 4990 - Q 5320

APRIL 2022

Equipment	NEES 2 + HSA	€ 1.854
-----------	--------------	---------

Standard features

<ul style="list-style-type: none"> • EGR - DPD - SCR • MID display • Air conditioning • Speed limiter (90km/h) • Engine exhaust brake • Power operated windows • Air spring seat 	<ul style="list-style-type: none"> • Seat belt buzzer • Cab overturning safety • Side mirrors heated and electric • Steering adjustable (tilting and height) • Radio DAB+ with USB • Immobilizer • variable SLD 	<ul style="list-style-type: none"> • Head lamps control levelling • Central locking with remote control • Cruise control • Day-time running lights • Front led lights • Fog lamps Fr and Rr
---	--	---

Engine

ISUZU 4HK1E6H 4 cylinders.
 common rail direct-injection intercooler with Twin-Turbocharger, additional injector on exhaust pipe.
 DISPLACEMENT 5193 cm³
 POWER 177kW (240 hp) 2400 rpm
 TORQUE 765 Nm - 1600 rpm
 EMISSIONS REGULATIONS EURO VI OBD-E.

Safety systems

ABS
ESC (Electronic Stability Control) with ASR
 LDWS
 AEBS
 SRS Driver Airbag

Tank

140 L

16 L Ad-Blue®

Gearbox and Final drive ratio

6 gear MZW6P – 6.615 - 4.095 - 2.358 - 1.531 - 1.000 - 0.722;
 Reverse 6.615;
 Final gear ratio 5.571 (39/7)

Transmission control

Manual

NEES 2 + Kick down

Dimensions of the chassis

Width 60 mm, Height 225 mm, Thickness 6 mm

Number of seats

3

Tires

Front: 265/70 R19,5C simple.
 Rear 265/70 R19,5C dual

Brakes

Front and rear drum brakes. To EEC standards with 4-channel ABS, Full Air pneumatic system with two independent circuits and EBS (Brake by wire) electronic control. Engine brake on the exhaust. Pneumatic parking brake on the rear axle.

Suspensions

Front: Multi taper leaf spring. Rear: 4-bag Air Suspension with height control. Front and rear stabilizer shaft.

Electric system

2 battery 110 A - System 24V - Generator 90A

PROVISIONAL VERSION: All data must be confirmed by the type approval certificate.