


OBD-E



P 75		P 75 F	P 75 H	P 75 K	P 75 M
Wheelbase	F	2765	3365	3815	4475
Overall length	OAL	5440	6040	6690	7870
Body lenght min. ⁽¹⁾	W	3660	4260	4910	6090
Body lenght Max. ⁽¹⁾	W	4000	4600	5250	6430
Rear overhang	ROH	1565	1565	1765	2285
Chassis height	EH	800			
Overall height	OH	2265			
Rear axle width	BW	2115			
Cab width ⁽²⁾	OW	2040			
Body width ⁽³⁾	6,1	2345			
Front axle to back of cab	D min	670 ⁽⁶⁾			
Front overhang	FOH	1110			
Frame internal size	LaC	850			
Front track	AW	1680			
Rear track	CW	1650			
Minimum Road Clearance	HH	185 ⁽⁷⁾			
Turning diameter (m) ⁽⁴⁾	Dia	10,6	12,6	14,1	16,3
WEIGHT (kg)					
Unladen weight ⁽⁵⁾		2720	2720	2740	2780
Unladen weight front axle		1750/970	1750/970	1770/970	1835/945
Gross Vehicle Weight (GVW)		7500			
Front/rear total weight		3100 / 5800			
Max trailer weight braked/ Max trailer weight unbraked		3500 / 750			

- The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
- Excluding turn signal and side mirrors
- Possible widths with optional mirror brackets 2115/2170 – 2170/2345 – 2345/2465
- Curb to curb turning diameter
- The Unladen weight include spare wheel, full fuel tank and driver, optional excluded. NEES II + 35 kg.
- With minimum counterframe height = 100 mm
- Clearance point: rear differential

PROVISIONAL VERSION: All data must be confirmed by the type approval certificate.

P 75 - Wheelbase (mm) F 2765 - H 3365 - K 3815 - M 4475

JANUARY 2024

Equipment	NEES 2	
	Right-hand drive (Wheelbase F NEES)	

Standard features		
<ul style="list-style-type: none"> • EGR - DPD - SCR • MID display • Engine exhaust brake • Side mirrors heated and electric • Immobilizer • Seat belt buzzer 	<ul style="list-style-type: none"> • Central locking with remote control • Suspended seat • Fog lamps Fr and Rr • Radio DAB+, USB, Bluetooth • Head lamps control levelling • Power operated windows 	<ul style="list-style-type: none"> • Day-time running lights • Front led lights • Automatic headlight lighting • Steering adjustable (tilting and height) • Speed limiter (90km/h) • Cab overturning safety

Optional	• Air conditioning	
----------	--------------------	--

Engine	<p>ISUZU 4JZ1E6N 4 cylinders.</p> <p>16 v with exhaust variable valve timing and gearing cascade distribution. DENSO i-Art Common rail injection system with VGS turbo (electronic control) and intercooler.</p> <p>DISPLACEMENT 2999 cm³ POWER 110kW (150 hp) 2800 rpm TORQUE 375 Nm 1280 – 2800 rpm EMISSIONS REGULATIONS EURO VI OBD-E.</p>
--------	--

Safety systems	<p>ABS</p> <p>ESC (Electronic Stability Control) with ASR</p> <p>LDWS</p> <p>AEBS (pedestrian recognition)</p> <p>SRS 2 Airbag (Driver/Pass.)</p>
----------------	--

Tank	90 L	14 L Ad-Blue®
------	------	---------------

Gearbox and Final drive ratio	6 gear MYY6Z – 5.979 - 3.434 – 2.040 - 1.379 - 1.000 - 0.708; Reverse 5.701; Final gear ratio 5.571 (39/7)
-------------------------------	--

Transmission control	Manual	NEES 2
----------------------	--------	--------

Dimensions of the chassis	Width 70 mm, Height 216 mm, Thickness 6 mm
---------------------------	--

Number of seats	3
-----------------	---

Axle	2 the rear one with twin wheels.
------	-------------------------------------

Tires	Front 215/75 R17,5C simple. Rear 215/75 R17,5C dual.
-------	---

Brakes	Front and rear: ventilated discs with asbestos-free linings. Hydraulic system, with vacuum brake booster EEC standards with ABS, independent circuits on both axles. Drum parking brake on the transmission shaft.
--------	--

Suspensions	Front parabolic crossbows, rear semielliptical integrated by rubber end-of-stroke pads; hydraulic telescopic shock absorbers with double effect. Front and rear stabilizer bar.
-------------	---

Electric system	Nominal voltage 24V - Generator 90A - 2 x Battery 90Ah (Wheelbase F: 2x70Ah)
-----------------	--